

DIMENSIONS AND WEIGHTS

Class	Size	2	2-1/2	3	4	5	6	8	10	12	14	16	18	20	24	28	30	32	36	
150	L (RF)	178	190	203	229	254	267	292	330	356	381	406	432	457	508	610	610	660	711	
	L1(BW)	216	241	283	305	381	403	419	457	502	572	610	660	711	813	914	914	965	1016	
	L2(RTJ)	191	203	216	241	267	279	305	343	368	394	419	445	470	521	622	622	673	724	
	H(OPEN)	409	472	532	612	710	806	990	1186	1405	1615	1811	1986	2210	2698	3030	3317	3487	3825	
	W	200	200	250	250	300	300	350	450	500	460*	460*	460*	610*	610*	610*	610*	610*	760*	
	Weight	RF	20	30	36	53	71	85	136	220	323	387	553	660	810	1250	1931	2380	2490	3600
BW		17	26	29	46	66	77	116	202	294	350	506	575	720	1130	1765	2028	2280	3080	
300	L-L1 (RF-BW)	216	241	283	305	381	403	419	457	502	762	838	914	991	1143		1397			
	L2(RTJ)	232	257	298	321	397	419	435	473	518	778	854	930	1010	1165		1422			
	H(OPEN)	400	477	543	650	770	880	1037	1275	1438	1650	1840	2030	2240	2900		3540			
	W	200	250	250	300	300	350	450	500	560	460*	460*	610*	610*	610*		760*			
	Weight	RF	30	39	55	83	92	137	240	333	536	669	1010	1205	1720	2800		3786		
		BW	26	34	47	68	77	118	195	271	432	595	848	1025	1460	2294		3220		
600	L-L1 (RF-BW)	292	330	356	432		559	660	787	838	889	991	1092	1194	1397					
	L2(RTJ)	295	333	359	435		562	664	791	841	892	994	1095	1200	1407					
	H(OPEN)	474	553	593	713		970	1122	1330	1519	1730	1835	2290	2510	3022					
	W	250	250	300	350		500	560	720	610*	610*	610*	610*	760*	760*					
	Weight	RF	41	58	88	131		253	413	623	784	1288	1820	2150	2540	4080				
		BW	35	50	68	104		208	328	496	637	1120	1448	1828	2201	3360				
900	L-L1 (RF-BW)	368	419	381	457		610	737	838	965	1029	1130								
	L2(RTJ)	371	422	384	460		613	740	841	968	1038	1140								
	H(OPEN)	547	700	648	729		1041	1260	1590	1795	2025	2170								
	W	300	355	400	450		560	460*	610*	610*	760*	760*								
	Weight	RF	90	110	123	148		420	650	1160	1700	2300	2750							
		BW	82	93	108	122		359	566	980	1450	2000	2390							
1500	L-L1 (RF-BW)	368	419	470	546		705	832	991	1130	1257	1384								
	L2(RTJ)	371	422	473	549		711	841	1000	1146	1276	1407								
	H(OPEN)	574	700	806	887		1079	1370	1520	1651	1945	2250								
	W	350	400	450	560		305*	610*	760*	760*	760*	760*								
	Weight	RF	117	175	240	337		680	1228	2278	3260	4100	5960							
		BW	93	144	185	285		584	978	1990	2850	3320	4890							

*Manual gear operator is recommended