

DIMENSIONS AND WEIGHTS

Class	Size	2	2-1/2	3	4	5	6	8	10	12
150	L-L1(RF-BW)	203	216	241	292	356	406	495	622	698
	L2(RTJ)	216	229	254	305	368	419	508	635	711
	H(OPEN)	373	390	421	515	538	567	626	712	990
	W	200	250	250	300	300	350	400	450	610
	Weight	RF	22	29	42	64	77	105	154	288
BW		19	25	34	49	65	82	131	249	430
300	L-L1(RF-BW)	267	292	318	356	400	444	559	622	711
	L2(RTJ)	283	308	333	371	416	460	575	638	727
	H(OPEN)	398	436	462	560	620	694	982	1130	1049
	W	200	250	250	350	400	450	560	864	460*
	Weight	RF	31	43	57	86	130	168	280	385
BW		26	28	44	68	110	138	228	329	618
600	L-L1(RF-BW)	292	330	356	432		559	660	787	838
	L2(RTJ)	295	333	359	435		562	664	791	840
	H(OPEN)	425	502	521	620		886	932	1040	1280
	W	250	300	350	450		720	460*	610*	760*
	Weight	RF	39	58	73	120		327	482	700
BW		33	48	61	95		261	385	588	795
900	L-L1(RF-BW)	368	419	381	457		610	737		
	L2(RTJ)	371	422	384	460		613	740		
	H(OPEN)	240	260	260	320		382	530		
	W	350	400	450	560		460*	610*		
	Weight	RF	100	118	131	218		452	710	
BW		75	94	105	185		340	630		
1500	L-L1(RF-BW)	368	419	470	546		705	832		
	L2(RTJ)	371	422	473	549		711	841		
	H(OPEN)	592	660	692	907		1015	1145		
	W	350	400	450	460*		610*	610*		
	Weight	RF	112	141	228	336		822	720	
BW		84	115	183	277		715	615		

*Manual gear operator is recommended