

DIMENSIONS AND WEIGHTS

CLASS 150													
DN NPS	mm in	15	20	25	40	50	65	80	100	150	200	250	300
		1/2	3/4	1	1-1/2	2	2-1/2	3	4	6	8	10	12
L(RF)	mm	108	117	127	165	178	191	203	229	394	457	533	610
	in	4.25	4.6	5	6.5	7	7.5	8	9	15.5	18	21	24
L1(BW)	mm	140	152	165	190	216	241	283	305	457	521	559	635
	in	5.5	6	6.5	7.48	8.5	9.5	11.13	12	18	20.5	22	25
L2(RTJ)	mm	119	129.7	139.7	178	191	203	216	241	406	470	546	622
	in	4.69	5.11	5.5	6.9	7.5	8	8.5	9.5	16	18.5	21.5	24.5
H	mm	59	63	75	95	153	165	195	213	272	342	495	580
	in	2.3	2.5	2.95	3.74	6.02	6.5	7.68	8.39	10.7	13.5	19.5	22.85
Do(W)	mm	130	130	160	230	400	400	600	850	1100	1500	*350	*350
	in	5.1	5.1	6.3	9	15.74	15.74	23.62	33.46	43.3	59	13.8	13.8
RF BW	Kg	2.3	3	4.5	7	15	20	25	40	97	160	240	390
	Kg	2.0	2.5	3.8	5.8	12	17	21	36	92.8	154	227	365

CLASS 300											
DN NPS	mm in	15	20	25	40	50	65	80	100	150	200
		1/2	3/4	1	1-1/2	2	2-1/2	3	4	6	8
L(RF)	mm	140	152	165	190	216	241	283	305	403	502
	in	5.5	5.98	6.5	7.48	8.5	9.5	11.13	12	15.88	19.75
L1(BW)	mm	140	152	165	190	216	241	283	305	457	521
	in	5.5	5.98	6.5	7.48	8.5	9.5	11.13	12	18	20.5
L2(RTJ)	mm	151	164.7	177.7	202.7	232	257	298	321	419	518
	in	5.95	6.48	7	8	9.13	10.13	11.75	12.63	16.5	20.39
H	mm	59	63	75	107	153	165	195	213	272	342
	in	2.3	2.5	2.95	4.2	6.02	6.5	7.68	8.39	10.7	13.5
Do(W)	mm	130	130	160	230	400	400	600	850	1100	1500
	in	5.1	5.1	6.3	9	15.74	15.74	23.62	33.46	43.3	59
RF BW	Kg	2.5	3.5	5.5	10.5	20	25	31	52	118	200
	Kg	2.1	3	4.8	8.7	17	22	28	48	105	185

CLASS 600								
DN NPS	mm in	15	20	25	40	50	65	80
		1/2	3/4	1	1-1/2	2	2-1/2	3
L(RF)	mm	165	190	216	241	292	330	356
	in	6.5	7.48	8.5	9.5	11.5	13	14
L1(BW)	mm	165	190	216	241	292	330	356
	in	6.5	7.48	8.5	9.5	11.5	13	14
L2(RTJ)	mm	163.4	190	216	241	295	333	359
	in	6.43	7.48	8.5	9.5	11.63	13.13	14.13
H	mm	59	63	75	107	153	165	195
	in	2.3	2.5	2.95	4.2	6.02	6.5	7.68
Do(W)	mm	130	160	160	230	600	850	1250
	in	5.1	6.3	6.3	9	23.62	33.46	49.25
RF BW	Kg	7.5	10.5	14.5	18.5	38	56	66
	Kg	6	8.7	11	14.7	31	49	58

*Worm Gear or Electric actuator operated.