

DIMENSIONS AND WEIGHTS

CLASS 150												
DN NPS	mm in	15	20	25	40	50	65	80	100	150	200	250
		1/2	3/4	1	1-1/2	2	2-1/2	3	4	6	8	10
L(RF)	mm in	108	117	127	165	178	191	203	229	394	457	533
		4.25	4.6	5	6.5	7	7.5	8	9	15.5	18	21
L1(BW)	mm in	140	152	165	190	216	241	283	305	457	521	559
		5.5	6	6.5	7.48	8.5	9.5	11.13	12	18	20.5	22
L2(RTJ)	mm in	119	129.7	139.7	178	191	203	216	241	406	470	546
		4.69	5.11	5.5	6.9	7.5	8	8.5	9.5	16	18.5	21.5
H	mm in	59	63	75	95	153	165	195	213	272	342	495
		2.3	2.5	2.95	3.74	6.02	6.5	7.68	8.39	10.7	13.5	19.5
Do(W)	mm in	130	130	160	230	400	400	600	850	1100	1500	*350
		5.1	5.1	6.3	9	15.74	15.74	23.62	33.46	43.3	59	13.8
RF BW	Kg Kg	2.3	3	4.5	7	15	20	25	40	97	160	240
		2.0	2.5	3.8	5.8	12	17	21	36	92.8	154	227

CLASS 300												
DN NPS	mm in	15	20	25	40	50	65	80	100	150	200	
		1/2	3/4	1	1-1/2	2	2-1/2	3	4	6	8	
L(RF)	mm in	140	152	165	190	216	241	283	305	403	502	
		5.5	5.98	6.5	7.48	8.5	9.5	11.13	12	15.88	19.75	
L1(BW)	mm in	140	152	165	190	216	241	283	305	457	521	
		5.5	5.98	6.5	7.48	8.5	9.5	11.13	12	18	20.5	
L2(RTJ)	mm in	151	164.7	177.7	202.7	232	257	298	321	419	518	
		5.95	6.48	7	8	9.13	10.13	11.75	12.63	16.5	20.38	
H	mm in	59	63	75	107	153	165	195	213	272	342	
		2.3	2.5	2.95	4.2	6.02	6.5	7.68	8.39	10.7	13.5	
Do(W)	mm in	130	130	160	230	400	400	600	850	1100	1500	
		5.1	5.1	6.3	9	15.74	15.74	23.62	33.46	43.3	59	
RF BW	Kg Kg	2.5	3.5	5.5	10.5	20	25	31	52	118	200	
		2.1	3	4.8	8.7	17	22	28	48	105	185	

CLASS 600								
DN NPS	mm in	15	20	25	40	50	65	80
		1/2	3/4	1	1-1/2	2	2-1/2	3
L(RF)	mm in	165	190	216	241	292	330	356
		6.5	7.48	8.5	9.5	11.5	13	14
L1(BW)	mm in	165	190	216	241	292	330	356
		6.5	7.48	8.5	9.5	11.5	13	14
L2(RTJ)	mm in	163.4	190	216	241	295	333	359
		6.43	7.48	8.5	9.5	11.63	13.13	14.13
H	mm in	59	63	75	107	153	165	195
		2.3	2.5	2.95	4.2	6.02	6.5	7.68
Do(W)	mm in	130	160	160	230	600	850	1250
		5.1	6.3	6.3	9	23.62	33.46	49.25
RF BW	Kg Kg	7.5	10.5	14.5	18.5	38	56	66
		6	8.7	11	14.7	31	49	58

*Worm Gear of Electric actuator operated.