

DIMENSIONS AND WEIGHTS

Class	Size	2	2-1/2	3	4	5	6	8	10	12	14	16	18	20	24	30	36	
150	L-L1 (RF-BW)	203	216	241	292	330	356	495	622	698	787	864	978	978	1295	1524	1955	
	L2(RTJ)	216	229	254	305	343	368	508	635	711	800	876	991	991	1308	1537	1968	
	H(OPEN)	150	168	180	210	230	275	340	355	410	475	552	600	660	740	980	1035	
	Weight	RF	17	21	29	42	69	74	108	177	282	372	570	665	900	1359	2120	3344
		BW	13	171	24	36	57	62	96	158	238	324	483	548	782	1150	1890	2940
300	L-L1 (RF-BW)	267	292	318	356	400	444	533	622	711	838	864	978	1016	1346	1594		
	L2(RTJ)	283	308	333	371	416	460	549	638	727	854	879	994	1036	1368	1619		
	H(OPEN)	180	185	210	270	345	360	370	385	440	520	554	590	614	614	866		
	Weight	RF	21	32	43	61	84	131	213	384	449	680	840	1025	1320	1960	3270	
		BW	16	24	35	44	61	105	167	272	375	560	710	828	1070	1586	2830	
600	L-L1 (RF-BW)	292	330	356	432		559	660	787	838	889	991	1092	1194	1397			
	L2(RTJ)	295	333	359	435		562	664	791	841	892	994	1095	1200	1407			
	H(OPEN)	197	207	231	281		362	437	490	528	572	660	720	746	960			
	Weight	RF	36	49	68	111		230	416	673	875	944	1220	1620	2120	3100		
		BW	28	40	57	83		191	361	543	770	773	1015	1350	1750	2520		
900	L-L1 (RF-BW)	368	419	381	457		610	737	838	965	1029	1130						
	L2(RTJ)	371	422	384	460		613	740	841	968	1038	1140						
	H(OPEN)	240	260	260	320		382	530	560	590	630	700						
	Weight	RF	69	93	91	145		259	565	900	1200	1500	2130					
		BW	52	74	70	112		218	448	733	975	1240	1760					
1500	L-L1 (RF-BW)	368	419	470	546		705	832	991	1130								
	L2(RTJ)	371	422	473	549		711	841	1000	1146								
	H(OPEN)	310	310	330	355		400	530	560	650								
	Weight	RF	69	93	140	232		490	990	1490	1970							
		BW	49	74	111	185		375	803	1250	1625							

*Manual gear operator is recommended